

Technical Data Sheet

CODE 61731

NORDIK INTERNATIONAL PLUS 160/60

Ceiling fans




Certifications



TECHNICAL AND PERFORMANCE DATA

Fan diameter	160	giri_minuto	201
Frequency (Hz)	50	Max airflow (m ³ /h)	14000
Insulation class	I°	Max airflow (m ³ /min)	233,33
Max absorbed current (A)	0,33	Max flow speed (m/s)	1,34
Max absorbed power (W)	70	RPM	201
Voltage (V)	220-240	Service value (m ³ /min)/W	3,333
Weight (Kg)	6,90	Sound power Lw [dB(A)]	55,6

DIMENSIONS



Size A (mm)	Ø
	1524
Size B (mm)	Ø 230
Size C (mm)	495

PER INFORMAZIONI / FOR INFORMATION

ITALY

Pre Sales:

prevendita@vortice-italy.com

After Sales:

postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF

IRELAND

Sales Dept:

sales@vortice.ltd.uk

Technical Dept:

technical@vortice.ltd.uk

OTHER COUNTRIES

Sales Dept:

export@vortice-italy.com

After Sales:

after-sales@vortice-italy.com

Technical Data Sheet

CODE 61731

NORDIK INTERNATIONAL PLUS 160/60



Ceiling fans

DESCRIPTION

- Nominal diameter of blades 1600 mm
- Top and bottom motor covers moulded from heat-resistant and UV-resistant thermoplastic resin (ABS), colour white
- Wiring connections at end of ceiling rod concealed by domes moulded from impact- and UV-resistant PP, colour white.
- Single phase start capacitor motor with external rotor, and shaft turning in ball bearings.
- Maximum air flow: 14,000 m³/h.
- 3 sheet steel blades powder coated with scratch-resistant polyester, colour white.
- Steel ceiling rod with polyester powder coated finish, colour white, length 375 mm.
- Bag of accessories containing nuts and bolts required for assembly of blades, ceiling hook and rubber anti-vibration washer.
- Factory-prepared to accept Light Kit (optional), suitable for lamp rated 150W max with E27 screw fitting, or equivalent energy-saving lamp with E27 screw fitting.
- Speed selectable by way of control units (optional)

ACCESSORIES



SCNR5 UNIF.X NK SOFFITTO

Code 12955



SCNRL5 UNIF. X NK SOFFITTO

Code 12957



TELENORDIK 5T

Code 22387



PLUS LIGHT KIT (KIT LUCE)

Code 22415



KIT SCB5 (TRASF.5 V.)

Code 22483



C 2.5 (COMANDO EL. 2.5 A)

Code 12967



SC 503 B

Code 12801



PER INFORMAZIONI / FOR INFORMATION

ITALY

Pre Sales:
prevendita@vortice-italy.com
After Sales:
postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF IRELAND

Sales Dept:
sales@vortice.ltd.uk
Technical Dept:
technical@vortice.ltd.uk

OTHER COUNTRIES

Sales Dept:
export@vortice-italy.com
After Sales:
after-sales@vortice-italy.com



PSC-B

Code 22463



**KIT SCB
(TRASF.E.C.)**

Code 22481



**ASTA NK I 200
BIANCA**

Code 22032



**ASTA NK I 250
BIANCA**

Code 22033



**ASTA NK I 350
BIANCA**

Code 22042



**ASTA NK I 500
BIANCA**

Code 22051



**ASTA NK I 750
BIANCA**

Code 22074



**ASTA NK I 1000
BIANCA**

Code 22077